



クリオンパネルの「許容荷重-最大長さ」対応表

●屋根パネル

【全工場】

厚さ (mm)	幅 (mm)	長期正圧(積載・固定荷重)				短期正圧(積載・固定荷重+風圧力)				短期負圧(風圧力)			
		許容荷重 (N/m ²)	支点間距離 (mm)	持出し長さ (mm)	パネル長さ (mm)	許容荷重 (N/m ²)	支点間距離 (mm)	持出し長さ (mm)	パネル長さ (mm)	許容荷重 (N/m ²)	支点間距離 (mm)	持出し長さ (mm)	パネル長さ (mm)
80	600 ~ 300 (@10)	1,000	2,400	240	2,640	1,000	2,400	240	2,640	-1,000~-2,800 (@100)	2,400	240	2,640
		1,500	2,300	240	2,540	1,500	2,400	240	2,640	-2,900	2,370	240	2,610
		2,000	2,200	240	2,440	2,000	2,370	240	2,610	-3,000	2,330	240	2,570
		-	-	-	-	2,500	2,220	240	2,460	-3,100	2,300	240	2,540
		-	-	-	-	3,000	2,050	240	2,290	-3,200	2,280	240	2,520
		-	-	-	-	-	-	-	-	-3,300	2,250	210	2,460
		-	-	-	-	-	-	-	-	-3,400	2,210	170	2,380
		-	-	-	-	-	-	-	-	-3,500	2,180	130	2,310
		-	-	-	-	-	-	-	-	-3,600	2,140	0	2,140
		-	-	-	-	-	-	-	-	-3,700	2,110	0	2,110
		-	-	-	-	-	-	-	-	-3,800	2,080	0	2,080
		-	-	-	-	-	-	-	-	-3,900	2,050	0	2,050
-	-	-	-	-	-	-	-	-4,000	2,020	0	2,020		
100	600 ~ 300 (@10)	1,000	3,000	300	3,300	1,000	3,000	300	3,300	-1,000~-2,900 (@100)	3,000	300	3,300
		1,500	2,850	300	3,150	1,500	3,000	300	3,300	-3,000	2,970	300	3,270
		2,000	2,750	300	3,050	2,000	3,000	300	3,300	-3,100	2,920	300	3,220
		2,400	2,500	0	2,500	2,500	2,750	300	3,050	-3,200	2,870	300	3,170
		3,000	2,420	0	2,420	3,000	2,750	300	3,050	-3,300	2,830	300	3,130
		3,600	2,320	0	2,320	3,500	2,500	300	2,800	-3,400	2,790	260	3,050
		4,000	2,250	0	2,250	4,000	2,460	300	2,760	-3,500	2,750	210	2,960
		4,200	2,210	0	2,210	4,500	2,230	300	2,530	-3,600	2,710	160	2,870
		4,600	2,130	0	2,130	5,000	2,100	300	2,400	-3,700	2,670	120	2,790
		5,000	1,980	0	1,980	5,500	2,000	300	2,300	-3,800	2,640	0	2,640
		-	-	-	-	6,000	1,900	300	2,200	-3,900	2,600	0	2,600
		-	-	-	-	-	-	-	-	-4,000	2,570	0	2,570
120	600 ~ 300 (@10)	1,000	3,600	360	3,960	1,000	3,600	360	3,960	-1,000~-3,100 (@100)	3,600	360	3,960
		1,500	3,600	360	3,960	1,500	3,600	360	3,960	-3,200	3,590	360	3,950
		2,000	3,600	360	3,960	2,000	3,600	360	3,960	-3,300	3,540	360	3,900
		2,400	3,000	0	3,000	2,500	3,300	360	3,660	-3,400	3,490	300	3,790
		3,000	2,970	0	2,970	3,000	3,300	360	3,660	-3,500	3,440	240	3,680
		3,600	2,830	0	2,830	3,500	3,000	360	3,360	-3,600	3,380	190	3,570
		4,000	2,750	0	2,750	4,000	3,000	360	3,360	-3,700	3,340	130	3,470
		4,200	2,710	0	2,710	4,500	2,780	360	3,140	-3,800	3,300	0	3,300
		4,600	2,590	0	2,590	5,000	2,640	360	3,000	-3,900	3,250	0	3,250
		5,000	2,410	0	2,410	5,500	2,470	360	2,830	-4,000	3,210	0	3,210
		-	-	-	-	6,000	2,300	360	2,660	-	-	-	-
		-	-	-	-	-	-	-	-	-	-	-	-
150	600 ~ 300 (@10)	1,000	4,500	450	4,950	1,000	4,500	450	4,950	-1,000~-2,800 (@100)	4,500	450	4,950
		1,500	4,300	450	4,750	1,500	4,500	450	4,950	-2,900	4,440	450	4,890
		2,000	4,100	450	4,550	2,000	4,500	450	4,950	-3,000	4,370	450	4,820
		2,400	3,750	0	3,750	2,500	4,290	450	4,740	-3,100	4,290	450	4,740
		3,000	3,510	0	3,510	3,000	4,000	450	4,450	-3,200	4,230	450	4,680
		3,600	3,270	0	3,270	3,500	3,750	450	4,200	-3,300	4,170	450	4,620
		4,000	3,130	0	3,130	4,000	3,500	450	3,950	-3,400	4,100	390	4,490
		4,200	3,070	0	3,070	4,500	3,300	450	3,750	-3,500	4,050	320	4,370
		4,600	2,960	0	2,960	5,000	3,100	450	3,550	-3,600	3,990	270	4,260
		5,000	2,850	0	2,850	5,500	2,960	450	3,410	-3,700	3,930	230	4,160
		-	-	-	-	6,000	2,800	450	3,250	-3,800	3,880	190	4,070
		-	-	-	-	-	-	-	-	-3,900	3,830	160	3,990
-	-	-	-	-	-	-	-	-4,000	3,780	130	3,910		



t: 持出し長さ